


FIG 947 - TEE



SIZE RANGE / DIMENSIONS

CODE	SIZE mm	OD mm	ID mm	T	C	M
947/0015	15	21.7	16.1	2.8	25.4	25.4
947/0020	20	27.2	21.6	2.8	28.6	28.6
947/0025	25	34.0	27.6	3.2	38.1	38.1
947/0032	32	42.7	35.7	3.5	47.6	47.6
947/0040	40	48.6	41.6	3.5	57.2	57.2
947/0050	50	60.5	52.9	3.8	63.5	63.5
947/0065	65	76.3	67.9	4.2	76.2	76.2
947/0080	80	89.1	80.7	4.2	85.7	85.7
947/0090	90	101.6	93.2	4.2	95.3	95.3
947/0100	100	114.3	105.3	4.5	104.8	104.8
947/0125	125	139.8	130.8	4.5	123.8	123.8
947/0150	150	165.2	155.2	5.0	142.9	142.9
947/0200	*200	219.1	207.5	5.8	177.8	177.8
947/0250	*250	273.0	259.8	5.8	215.9	215.9
947/0300	*300	323.8	310.0	6.6	254	254
947/0350	350	355.6	339.8	6.9	279.4	279.4
947/0400	400	406.4	390.6	7.9	304.8	304.8
947/0450	450	457.2	441.4	7.9	342.9	342.9
947/0500	500	508.0	492.2	7.9	381	381
947/0550	550	558.8	543.0	7.9	419.1	419.1
947/0600	600	609.6	593.8	7.9	431.8	431.8

DIMENSIONAL TOLERANCES AND PERMISSIBLE VALUES

ITEM	TYPES OF PIPE FITTINGS	NOMINAL DIAMETER mm					
		15-65	80-100	125-200	250-450	500-600	650-750
TOLERANCE							
Outside diameter at end	All types of pipe fittings	± 2.0	± 2.5	± 3.5	+5.0 - 4.5	+6.4 - 4.8	
Inside diameter at end face		± 2.0	± 2.5	± 3.5	± 4.5	± 4.8	
Thickness		*not specified -15%					
Bevel angle		See Fig					
Height of root face		See Fig					
Dimensions from centerline to end face (H F)	45 ° Elbow 90 ° Elbow	± 2.0		± 3.2			
Overall length (H)	Reducers	± 2.0		± 3.2			± 4.8
Dimension from centerline to end face (C M)	Tees	± 2.0		± 3.2			± 4.8
Dimensions from back to end face (E)	Caps	± 3.2		± 6.4			-